




Position	Qty.	Description	Single Price
	1	<p>UPS 20-60 N 150</p>  <p>Note! Product picture may differ from actual product</p> <p>Product No.: 96913096 The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing. The bearings are lubricated by the pumped liquid. The pump has 3-step speed selector. The pump is characterized by:</p> <ul style="list-style-type: none"> * Ceramic shaft and radial bearings. * Carbon axial bearing. * Stainless steel rotor can and bearing plate. * Corrosion-resistant impeller, Composite, PES/PP. * Stainless steel pump housing. <p>The motor is a 1-phase motor. No additional motor protection is required.</p> <p>Liquid: Liquid temperature range: 2 .. 110 °C</p> <p>Technical: TF class: 110 Maximum operating pressure: 10 bar Approvals on nameplate: CE</p> <p>Materials: Pump housing: Stainless steel DIN W.-Nr. 1.4301 Impeller: Composite, PES/PP</p> <p>Installation: Amb. max at 80 dgr C liquid: 80 °C Maximum operating pressure: 10 bar Pipe connection: G 1 1/4 Pressure stage: PN 10 Port-to-port length: 150 mm</p> <p>Electrical data: Power input in speed 1: 35 W Power input in speed 2: 60 W Max. power input: 90 W Mains frequency: 50 Hz</p>	On request



Company name: -
Created by: -
Phone: -
Fax: -
Date: -

Position	Qty.	Description	Single Price
		Rated voltage: 1 x 240 V Current in speed 1: 0.15 A Current in speed 2: 0.25 A Current in speed 3: 0.37 A Capacitor size - run: 2 µF Enclosure class (IEC 34-5): 44 Insulation class (IEC 85): H Others: Net weight: 2.8 kg Gross weight: 3 kg Shipping volume: 0.004 m3 Energy label: D	



96913096 UPS 20-60 N 150 50 Hz

